

excelsior[®]
washrooms for all environments

Flush44 Cubicle Range

WASHROOMS FOR ALL ENVIRONMENTS



Flush44 Cubicle Range

The premium flush fronted cubicle solution

The Flush 44 cubicle range is the genuine 'premium quality' system, offering a sleek flush fronted facade, with surface finishes available in both HPL and Natural Veneer complete with hardwood edges to doors. Allowing the the most discerning specifier complete satisfaction in their selection.

At Excelsior we offer the Flush44 in three standard formats:

1. 2100mm overall proprietary height incorporating a 150mm pedestal leg and SAA box headrail.
2. Full height up to 2700mm as standard floor to ceiling option with 38mm divisions set into a 'U' section floor channel.
3. Full height 2700mm as standard floor to ceiling option with back to back duct panel divisions offering a 100mm service void.

All three formats incorporate Stainless Steel Ironmongery as Standard and are DDA compliant with outward opening

doors complete with 'D' handles to ease access where doors are set to fall closed.

Flush44 is available in several different surface finishes including High Pressure Laminate and Natural Wood Veneers complete with rebated Hardwood edges to all doors and pilasters.

Typical manufacturing period is 5-6 weeks from receipt of approved drawings and colour selection.

Installation by Excelsior is strongly recommended but not essential as a full set of fixing instructions and technical information is provided with the system.



Ironmongery

1. Large Turn
2. Indicator Faceplate
3. Rise & Fall Hinge



Flush44 Specifications

Flush 44 Cubicle (Floor to Ceiling)

Specifications

Doors and Pilasters:

- High Pressure Laminate PUR bonded onto 44mm MR core
- Rebated Hardwood Edges (Oak as standard). Sealed 2 coats AC Lacquer. Hardwood is a natural product and will not match a laminate finish.

Continuous Head Section:

- High Pressure Laminate bonded onto 44mm MR core
- Hardwood Edges, sealed 2 coats AC Lacquer

Natural veneers, digital print HPL and gloss HPL available at additional cost

Divisions Specification:

- High Pressure Laminate PUR bonded onto 36mm MR core
- Matching Laminate edge detail

Standard Dimensions:

- Upto 2700mm overall height x 1500mm deep (partitions to be jointed for manual handling)

Ironmongery:

- Continuous 'T' section Pilaster fixing channel
- Royde & Tucker D-Line Stainless Steel rise and fall hinges
- D-Line Eisenware Large Turn and Release SSS - 14347802300
- Deadbolt (4871.01) with Excelsior Wrap striking plate/keep
- 38mm 'U' section SAA floor channel
- Hat & Coat hook 90mm c/w buffer T500
- Rear Wall 'T' section division fixing channel
- 3mm door/pilaster cushion gasket

Toilet Roll Holders & Accessories available upon request.

Flush 44 Cubicle (2100mm High)

Specifications

Doors and Pilasters:

- High Pressure Laminate PUR bonded onto 44mm MR core
- Rebated Hardwood Edges (Oak as standard). Sealed 2 coats AC Lacquer. Hardwood is a natural product and will not match a laminate finish.

Natural veneers, digital print HPL and gloss HPL available at additional cost

Divisions Specification:

- High Pressure Laminate PUR bonded onto 18mm MR core
- Matching Laminate edge detail

Standard Dimensions:

- 2100mm overall height x 1500mm deep. C/W 150mm leg

Ironmongery:

- Continuous 'T' section Pilaster fixing channel
- Royde & Tucker D-Line Stainless Steel rise and fall hinges
- D-Line Eisenware Large Turn and Release SSS - 14347802300
- Deadbolt (4871.01) with Excelsior Wrap striking plate/keep
- Leg 150mm - Ref: EXL - A150 SBAA Finish
- Hat & Coat hook 90mm c/w buffer T500
- Rear Wall 'T' section division fixing channel
- 3mm door/pilaster cushion gasket
- Headrail - T-Line 38mm U Section headrail SAA
- Headrail End Caps - Ref: 38mm end

Toilet Roll Holders & Accessories available upon request.



1. Protective overlay for printed decors.
2. Decorative paper impregnated with melamine resin.
3. Layers of kraft paper impregnated with phenolic resin, to be bonded onto MR core.

HPL - High Pressure Laminate

High pressure laminate (bonded onto a chipboard or MDF substrate. These core materials offer water resistance only (they are not waterproof) offers heat, scratch and impact resistance with edges finished with a colour match or contrast 2mm PVC detail.

Comfortable in school, office, entertainment, health and retail environments alike.

Ironmongery Finish: Stainless Steel as standard.

Colour Selections: Excelsior preferred cubicle & washroom colour selection or natural veneer.

Special Notes: Outward opening doors complete with back to back Stainless Steel 'D' Handles.

N.B. Hardwood edges will be light oak as standard which may result in a colour variance to the face.

We recommend that outward opening doors open onto an adjacent solid wall to prevent overstrain on hinges.

